

---

# EmCORE-i230G

**3.5" Compact Board**

## **User's Manual**

**Version 1.1**

CE



2017.05

---

---

This page is intentionally left blank.

---

---

## Revision History

Version	Release Time	Description
1.0	April, 2015	Initial release
1.1	May, 2017	Added supported SDXC information in <a href="#">1.3. Specifications</a> and <a href="#">2.3.3. Connectors</a> SD1 section

---

This page is intentionally left blank.

<b>Revision History .....</b>	<b>i</b>
<b>Table of Contents .....</b>	<b>iii</b>
<b>Preface.....</b>	<b>v</b>
Copyright Notice .....	v
Declaration of Conformity .....	v
CE.....	v
FCC Class A .....	vi
RoHS .....	vi
SVHC / REACH .....	vii
Warning.....	vii
Replacing Lithium Battery .....	vii
Technical Support .....	vii
Warranty.....	viii
<b>Chapter 1 - Introduction.....</b>	<b>1</b>
1.1. The Product .....	2
1.2. About this Manual .....	2
1.3. Specifications.....	3
1.4. Inside the Package .....	4
1.5. Ordering Information .....	4
<b>Chapter 2 - Getting Started.....</b>	<b>5</b>
2.1. Board Dimensions .....	6
2.1.1. SKU-E3825.....	6
2.1.2. SKU-E3845.....	7
2.2. Block Diagram.....	8
2.3. Jumpers & Connectors .....	9
2.3.1. Layout.....	9
2.3.2. Jumpers.....	11
2.3.3. Connectors .....	16
2.4. Driver Installation Notes.....	41
<b>Chapter 3 - BIOS.....</b>	<b>43</b>
3.1. Main .....	45
3.2. Advanced .....	46
3.2.1. Boot Configuration .....	47
3.2.2. PCI Express Configuration .....	47
3.2.3. USB Configuration .....	47
3.2.4. Video Configuration .....	48
3.2.5. SATA Configuration.....	49
3.2.6. ACPI Table/Feature Control .....	49
3.2.7. SIO FINTEK71869E .....	50

3.3. Security .....	51
3.4. Power .....	52
3.5. Boot .....	53
3.6. Exit .....	54
<b>Appendices .....</b>	<b>55</b>
Appendix A. Watchdog Timer (WDT) Setting .....	56
Appendix B. Digital I/O Setting.....	57
Appendix C: I/O Port Address Map .....	59
Appendix D: Interrupt Request Lines (IRQ) .....	61
Appendix E: Memory Mapping.....	62

## Copyright Notice

All Rights Reserved.

The information in this document is subject to change without prior notice in order to improve the reliability, design and function. It does not represent a commitment on the part of the manufacturer.

Under no circumstances will the manufacturer be liable for any direct, indirect, special, incidental, or consequential damages arising from the use or inability to use the product or documentation, even if advised of the possibility of such damages.

This document contains proprietary information protected by copyright. All rights are reserved. No part of this manual may be reproduced by any mechanical, electronic, or other means in any form without prior written permission of the manufacturer.

## Declaration of Conformity

### CE

The CE symbol on your product indicates that it is in compliance with the directives of the Union European (EU). A Certificate of Compliance is available by contacting Technical Support.

This product has passed the CE test for environmental specifications when shielded cables are used for external wiring. We recommend the use of shielded cables. This kind of cable is available from ARBOR. Please contact your local supplier for ordering information.

This product has passed the CE test for environmental specifications. Test conditions for passing included the equipment being operated within an industrial enclosure. In order to protect the product from being damaged by ESD (Electrostatic Discharge) and EMI leakage, we strongly recommend the use of CE-compliant industrial enclosure products.

### Warning

This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

### **FCC Class A**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

#### **NOTE:**

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

### **RoHS**

ARBOR Technology Corp. certifies that all components in its products are in compliance and conform to the European Union's Restriction of Use of Hazardous Substances in Electrical and Electronic Equipment (RoHS) Directive 2002/95/EC.

The above mentioned directive was published on 2/13/2003. The main purpose of the directive is to prohibit the use of lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB), and polybrominated diphenyl ethers (PBDE) in electrical and electronic products. Member states of the EU are to enforce by 7/1/2006.

ARBOR Technology Corp. hereby states that the listed products do not contain unintentional additions of lead, mercury, hex chrome, PBB or PBDB that exceed a maximum concentration value of 0.1% by weight or for cadmium exceed 0.01% by weight, per homogenous material. Homogenous material is defined as a substance or mixture of substances with uniform composition (such as solders, resins, plating, etc.). Lead-free solder is used for all terminations (Sn(96-96.5%), Ag(3.0-3.5%) and Cu(0.5%)).



## **SVHC / REACH**

To minimize the environmental impact and take more responsibility to the earth we live, Arbor hereby confirms all products comply with the restriction of SVHC (Substances of Very High Concern) in (EC) 1907/2006 (REACH --Registration, Evaluation, Authorization, and Restriction of Chemicals) regulated by the European Union.

All substances listed in SVHC < 0.1 % by weight (1000 ppm)

## **Warning**

Single Board Computers and their components contain very delicate Integrated Circuits (IC). To protect the Single Board Computer and its components against damage from static electricity, you should always follow the following precautions when handling it :

1. Disconnect your Single Board Computer from the power source when you want to work on the inside.
2. Hold the board by the edges and try not to touch the IC chips, leads or circuitry.
3. Use a grounded wrist strap when handling computer components.
4. Place components on a grounded antistatic pad or on the bag that comes with the Single Board Computer, whenever components are separated from the system.

## **Replacing Lithium Battery**

Incorrect replacement of the lithium battery may lead to a risk of explosion.

The lithium battery must be replaced with an identical battery or a battery type recommended by the manufacturer.

Do not throw lithium batteries into the trash-can. It must be disposed of in accordance with local regulations concerning special waste.

## **Technical Support**

If you have any technical difficulties, please do not hesitate to call or e-mail our customer service.

<http://www.arbor-technology.com>

E-mail: [info@arbor.com.tw](mailto:info@arbor.com.tw)

## **Warranty**

This product is warranted to be in good working order for a period of two years from the date of purchase. Should this product fail to be in good working order at any time during this period, we will, at our option, replace or repair it at no additional charge except as set forth in the following terms. This warranty does not apply to products damaged by misuse, modifications, accident or disaster.

Vendor assumes no liability for any damages, lost profits, lost savings or any other incidental or consequential damage resulting from the use, misuse of, or inability to use this product. Vendor will not be liable for any claim made by any other related party.

Vendors disclaim all other warranties, either expressed or implied, including but not limited to implied warranties of merchantability and fitness for a particular purpose, with respect to the hardware, the accompanying product's manual(s) and written materials, and any accompanying hardware. This limited warranty gives you specific legal rights.

Return authorization must be obtained from the vendor before returned merchandise will be accepted. Authorization can be obtained by calling or faxing the vendor and requesting a Return Merchandise Authorization (RMA) number. Returned goods should always be accompanied by a clear problem description.


---

# Chapter 1

## Introduction

## 1.1. The Product

- Support Intel® Atom™ Processor E3800 family
- Integrated Gigabit Ethernet
- LVDS, Analog RGB Port, HDMI port
- Support Dual Independent Displays
- Soldered Onboard eMMC (OEM request)
- **Wide Range Operating Temp.: -40 ~ 85°C**



## 1.2. About this Manual

This manual is intended for experienced users and integrators with hardware knowledge of computers. If you are not sure about the description in this manual, consult your vendor before further handling.

We recommend that you keep one copy of this manual for the quick reference for any necessary maintenance in the future. Thank you for choosing ARBOR products.

### 1.3. Specifications

<b>Form Factor</b>	3.5" Compact Board
<b>CPU</b>	Soldered onboard Intel® Atom™ Processor E3825 1.33GHz or E3845 1.91GHz
<b>System Memory</b>	1 x DDR3L SO-DIMM socket, supporting up to 8GB 1333/1600 MT/s SDRAM
<b>Graphics Chipset</b>	Integrated Intel® HD Graphics
<b>Graphics Interface</b>	Analog RGB with resolution up to 2048x1536, HDMI
	LVDS: Dual Channels 24-bit LVDS, with resolution up to 1920x1200
<b>Ethernet</b>	2 x Realtek® RTL8111 PCIe GbE controllers
<b>BIOS</b>	Insyde BIOS
<b>Audio</b>	Realtek ALC662 HD Audio CODEC, MIC-in/ Line-out/Line-in
<b>Storage</b>	1 x Serial ATA port with 300MB/s HDD transfer rate
	1 x CFast socket
	4GB/ 8GB/ 16GB eMMC 4.5 (OEM request)
<b>Serial Port</b>	2 x RS-232/485 selectable
<b>USB 2.0</b>	6 x USB 2.0 ports
<b>USB 3.0/2.0</b>	1 x USB 3.0/2.0 port
<b>Digital I/O</b>	8-bit Programmable
<b>Expansion Bus</b>	1 x Mini-card socket (Full size)
	1 x Micro-SDXC socket (supports SDXC card SD 3.0 only)
	1 x micro SIM socket
<b>Power Requirement</b>	DC 12V
<b>Power Consumption</b>	0.83A@+12V with E3845 (Typical)
<b>Operating Temp.</b>	-40°C ~ 85°C (-40°F ~ 185°F)
<b>Operating Humidity</b>	10% ~ 95% @ 85°C (non-condensing)
<b>Watchdog Timer</b>	1~255 levels reset
<b>Dimension (L x W)</b>	146 x 102 mm (5.7" x 4.0")

## 1.4. Inside the Package

Before starting to install the single board, make sure the following items are shipped:



1 x EmCORE-i230G 3.5" Compact Board with heatsink



1 x Driver CD



1 x Quick Installation Guide

If any of the aforelisted items is damaged or missing, contact your vendor immediately.

## 1.5. Ordering Information

<b>EmCORE-i230G-E3825</b>	Intel® Atom™ Processor E3825 3.5" Compact Board
<b>EmCORE-i230G-WT-E3825 (BTO)</b>	Wide range temperature Intel® Atom™ Processor E3825 3.5" Compact Board
<b>EmCORE-i230G-E3845</b>	Intel® Atom™ Processor E3845 3.5" Compact Board
<b>EmCORE-i230G-WT-E3845 (BTO)</b>	Wide range temperature Intel® Atom™ Processor E3845 3.5" Compact Board
<b>CBK-08-230G-00</b>	Cable kit 1 x AUDIO cable 2 x COM port latching cables 1 x Keyboard & mouse latching y-cable 1 x SATA cable 1 x SATA power cable 2 x USB cables


---

# Chapter 2

## Getting Started


## 2.1. Board Dimensions

### 2.1.1. SKU-E3825






2.1.2. SKU-E3845



## 2.2. Block Diagram




## 2.3. Jumpers & Connectors

The board comes with some connectors to join some devices and also some jumpers to alter the hardware configuration. The following in this chapter will explicate each of these components one-by-one.


### 2.3.1. Layout

This section will provide an overview of this board, both the top and bottom sides.

#### Board Top



## Board Bottom



## 2.3.2. Jumpers

### JPIC1

**Function:** AT/ATX Power Mode Selection

**Jumper Type:** 2.00mm pitch 2x3-pin header

**Setting:**

Pin	Description
-----	-------------


2-4	AT
-----	----



4-6	ATX mode (default)
-----	--------------------



### Board Top



## JVLCD1

**Function:** LCD Panel Voltage Selection

**Jumper Type:** 2.54mm pitch 1x3-pin header

**Setting:**

Pin	Description
-----	-------------


1-2	+5V
-----	-----



2-3	+3.3V (default)
-----	-----------------



## Board Top



## JINV1

**Function:** LCD Inverter Voltage Selection

**Jumper Type:** 2.54mm pitch 1x3-pin header

**Setting:**

Pin	Description
-----	-------------


1-2	+12V
-----	------



2-3	+5V (default)
-----	---------------



## Board Top







## JRS1

**Function:** COM1&2 RS-232/485 Selection


**Jumper Type:** 2.00 mm pitch 2x3-pin header

**Setting:**

Pin	Description	
1-3	COM1=RS-232 (default)	
3-5	COM1=RS-485	
2-4	COM2=RS-232 (default)	
4-6	COM2=RS-485	

**Note:** To enable RS-485 CON1, beside jumper setting, please go to BIOS Setting Menu to Enable RS-485 mode of COM1&2. Option is under **Advanced/ SIO FINTEK71869E/ RS-232/485 Setting/ RS-485**.

## Board Top










## JRS2

**Function:** COM1&2 RS-485 Terminator Mode Selection

**Jumper Type:** 2.00 mm pitch 2x2-pin header

Setting:	Pin	Status	Description	
1-2	1-2	Open	Set COM1 to RS-485 Terminator Mode (default)	
		Short	Set COM1 to RS-485 Normal Mode	
3-4	3-4	Open	Set COM2 to RS-485 Terminator Mode (default)	
		Short	Set COM2 to RS-485 Normal Mode	

## Board Top



### 2.3.3. Connectors

#### 12VIN1

**Function:** ATX +12V Connector


**Connector Type:** 4-pin power connector

**Pin Assignment:**

Pin Description	Pin Description
4 +12V	3 +12V
2 GND	1 GND



#### Board Top




## JFRT1

**Function:** Provides connectors to front-panel status LED and toggles


**Connector Type:** 2.54mm pitch 2x5-pin header

**Pin Assignment:**

Pin	Description	Pin	Description
1	RESET+	2	RESET-
3	PLED+	4	PLED-
5	HLED+	6	HLED-
7	SPEAK+	8	SPEAK-
9	PSON+	10	PSON-



## Board Top




## FAN1

**Function:** Fan connector


**Connector Type:** 2.54mm pitch 1x3-pin wafer connector.

**Pin Assignment:**

Pin	Description
1	GND
2	+12V
3	Speed



### Board Top




## KBMS1

**Function:** Keyboard & Mouse connector


**Connector Type:** 2.0mm pitch 1x6-pin header

**Pin Assignment:**

Pin	Description
1	KB_DATA
2	GND
3	MS_DATA
4	KB_CLK
5	PS2_VCC
6	MS_CLK



## Board Top



## INV1

**Function:** LCD inverter connector


**Connector Type:** 2.00mm pitch 1x5-pin box wafer

**Pin Assignment:**

Pin	Description
1	Vin
2	GND
3	on/off
4	Brightness control
5	GND



## Board Top




## LVDS1

**Function:** LVDS LCD panel connector


**Connector Type:** ACES 1.25mm 87209-3040-06 connector that supports 24-bit dual channels.

**Pin Assignment:**

Pin Description	Pin Description
2 VDD	1 VDD
4 TX2_CLK+	3 TX1_CLK+
6 TX2_CLK-	5 TX1_CLK-
8 GND	7 GND
10 TX2_D0+	9 TX1_D0+
12 TX2_D0-	11 TX1_D0-
14 GND	13 GND
16 TX2_D1+	15 TX1_D1+
18 TX2_D1-	17 TX1_D1-
20 GND	19 GND
22 TX2_D2+	21 TX1_D2+
24 TX2_D2-	23 TX1_D2-
26 GND	25 GND
28 TX2_D3+	27 TX1_D3+
30 TX2_D3-	29 TX1_D3-



## Board Top




### SIM1

**Function:** micro-SIM card socket


**Connector Type:** REGO 80440GIH-061T-120L socket

**Pin Assignment:**

Pin Description	Pin Description
C1 VCC	C2 RST
C3 CLK	C5 GND
C6 VPP	C7 I/O



### Board Top





## BAT1

**Function:** Battery connector


**Connector Type:** 1.25mm pitch 1x2 pin wafer connector

**Pin Assignment:**

Pin	Description
1	GND
2	Battery Power



## Board Top



## CON1

**Function:** RS-485 connector

**Connector Type:** 2.00mm pitch 1x4-pin wafer connector


**Pin Assignment:**

Pin	Description
1	COM1 DATA1 +
2	COM1 DATA1 -
3	COM2 DATA2 +
4	COM2 DATA2 -



Note: To enable this port, please refer to [JRS1](#) on page [14](#) .

## Board Top




## USB1,4

**Function:** USB 2.0 connector


**Connector Type:** 2.00mm pitch 2x5-pin lockable box headers

**Pin Assignment:**

Pin	Description	Pin	Description
2	+5V	1	+5V
4	USBP1-	3	USBP0-
6	USBP1+	5	USBP0+
8	GND	7	GND
10	GND	9	GND



## Board Top




## COM1&2

**Function:** Serial port connector


**Connector Type:** 2.00mm pitch 2x5-pin wafer connector

**Pin Assignment:**

Pin	Description	Pin	Description
2	RX	1	DCD#
4	DTR#	3	TXD
6	DSR#	5	GND
8	CTS#	7	RTS#
10	N/C	9	RI#



### Board Top




## DIO1

**Function:** Digital I/O connector


**Connector Type:** 2.00mm pitch 2x5-pin lockable box headers

**Pin Assignment:**

Pin	Description	Pin	Description
2	GPIO1	1	GPIO0
4	GPIO3	3	GPIO2
6	GPIO5	5	GPIO4
8	GPIO7	7	GPIO6
10	GND	9	+5V



## Board Top



DIO1


## AUDIO1

**Function:** Audio connector


**Connector Type:** 2.00mm pitch 2x5-pin header

**Pin Assignment:**

Pin Description	Pin Description
1 Line Left In	2 Line Right In
3 GND	4 GND
5 MIC1	6 MIC2
7 GND	8 GND
9 Line-out Left	10 Line-out Right



### Board Top



AUDIO1


## SATA1

**Function:** Serial ATA connector

**Pin Assignment:** The pin assignments conform to the industry standard.



## Board Top



SATA1

## PWROUT1

**Function:** SATA power connector


**Connector Type:** 2.00mm pitch 1x4-pin wafer connector

**Pin Assignment:**

Pin	Description
1	VCC 5V
2	GND
3	GND
4	VCC 12V



## Board Top



PWROUT1




## LAN1, 2

**Function:** Ethernet connectors


**Connector Type:** RJ-45 connector that supports 10/100/1000Mbps Ethernet

**Pin Assignment:**

Pin	Description	Pin	Description
1	MDI0+	2	MDI0-
3	MDI1+	4	MDI1-
5	MDI2+	6	MDI2-
7	MDI3+	8	MDI3-




### Board Top



## RES1

Function: Reset button

### Board Top





## HDMI1

**Function:** HDMI connector

**Connector Type:** 19-pin HDMI connector with flange

**Pin Assignment:** The pin assignments conform to the industry standard.

### Board Top



## USB2


**Function:** USB 3.0 connector

**Connector Type:** USB 3.0/2.0 type-A connectors

**Pin Assignment:** The pin assignments conform to the industry standard.



## Board Top




## USB3


**Function:** Double-stacked USB connectors

**Connector Type:** Two USB 2.0/1.0 type-A connectors

**Pin Assignment:** The pin assignments conform to the industry standard.



## Board Top




## VGA1

**Function:** Analog RGB connector


**Connector Type:** D-Sub 15-pin female connector

**Pin Assignment:**

Pin	Description.	Pin	Description
1	RED	9	5V
2	GREEN	10	GND
3	BLUE	11	N/C
4	N/C	12	D-DATA
5	GND	13	H-SYNC
6	GND	14	V-SYNC
7	GND	15	D-DCLK
8	GND		




### Board Top



**SYSLED1:**

Function: Power ON & HDD LED Indicator

**Board Top**



## MC1


**Function:** Mini-card socket

**Connector Type:** Onboard 0.8mm-pitch 52-pin edge card connector interconnected with SIM card socket.

The pin assignments conform to the industry standard.



## Board Bottom






## CF1


**Function:**

CFast card socket

The pin assignments conform to the industry standard.



## Board Bottom




---


## SD1

**Function:** Micro SDXC card socket  
(supports SDXC card SD 3.0 only)

The pin assignments conform to the industry standard.



## Board Bottom



---

## 2.4. Driver Installation Notes

The board supports Windows 7 and Windows 8.1. Find the necessary drivers on the CD that comes with your purchase. For different OS, the driver/utility installation may vary slightly, but generally they are similar.

Find the drivers on CD by the following paths:

### Windows 7

Device	Driver Path
<b>Audio</b>	\\Audio\32bit_Win7_Win8_Win81_R275
	\\Audio\64bit_Win7_Win8_Win81_R275
<b>Chipset</b>	\\Chipset\SetupChipset_10.0.13_PC
<b>Ethernet</b>	\\Ethernet\Realtek\Win7\Install_Win7_7085_05222014
<b>GPIO</b>	\\GPIO\windows 7 32_64\Intel Atom E3800 Win7 IO Drivers_Gold_v1.0 package 501232_20140211
<b>Graphic</b>	\\Graphics\WIN7_32\Intel_EMGD.WIN7_PC_Version_36_15_0_1073
	\\Graphics\WIN7_64\Intel_EMGD.WIN7_PC_Version_37_15_0_1073
<b>TXE</b>	\\TXE\Installers (Only for 64-bit)
<b>USB3.0</b>	\\USB3.0\Intel(R) USB 3.0 eXtensible Host Controller_Win7_32bit_64bit_R3.0.0.33
<b>Serial IO</b>	\\Serial IO\Intel Processor IO Drivers_Win7_32bit_64bit_Gold_v2.0

### Windows 8.1

Device	Driver Path
<b>Audio</b>	\\Audio\32bit_Win7_Win8_Win81_R275
	\\Audio\64bit_Win7_Win8_Win81_R275
<b>Chipset</b>	\\Chipset\SetupChipset_10.0.13_PC
<b>Ethernet</b>	\\Ethernet\Realtek\Win8_8.1\Install_Win8_8.1_8031_05222014
<b>GPIO</b>	\\GPIO\Kit 100882 20140211 windows 8.1 64\GPIO(Only for 64-bit)
<b>Graphic</b>	\\Graphics\WIN8_32\15.33.22.3621
	\\Graphics\WIN8_64\15.33.22.64.3621
<b>TXE</b>	\\TXE\Installers
<b>Serial IO</b>	\\Serial IO\SerialIO_Installer_Win8.1_64bit_WW23

---

This page is intentionally left blank.

---

# Chapter 3

## BIOS

## BIOS

---

The BIOS Setup utility is featured by BIOS to configure the system settings stored in the system's BIOS ROM. BIOS is activated once the computer powers on.


After entering the utility, use the left/right arrow keys to navigate between the top menus and use the down arrow key to access one.

Menu	Description
<b>Main</b>	See <a href="#">3.1. Main</a> on page <a href="#">45</a> .
<b>Advanced</b>	See <a href="#">3.2. Advanced</a> on page <a href="#">46</a> .
<b>Security</b>	See <a href="#">3.3. Security</a> on page <a href="#">51</a> .
<b>Power</b>	See <a href="#">3.4. Power</a> on page <a href="#">53</a> .
<b>Boot</b>	See <a href="#">3.5. Boot</a> on page <a href="#">53</a> .
<b>Exit</b>	See <a href="#">3.6. Exit</a> on page <a href="#">54</a> .

NOTE: For system stability and performance, this BIOS utility is constantly improved. The screenshots demonstrated and descriptions hereinafter are for reference only and may not exactly meet what is presented onscreen.

### 3.1. Main

The **Main** menu displays some BIOS info and features the settings of **System Date** and **System Time**.



The BIOS info displayed is:


Info Item	Description
<b>BIOS Version</b>	Delivers the computer's BIOS version.
<b>Project name</b>	Delivers the name of the project
<b>Build Date and Time</b>	Delivers the date and time when the BIOS Setup utility was created/updated.
<b>Platform firmware Information</b>	Delivers the Platform firmware Information

The featured settings are:

Setting	Description
<b>Language</b>	Select the current default language used by the InsydeH20
<b>System Time</b>	Sets system time.
<b>System Date</b>	Sets system date.

### 3.2. Advanced

The **Advanced** menu controls the system’s CPU, IDE, Super IO, AHCI and USB. It also helps users monitor hardware health.



The featured submenus are:

Submenu	Description
Boot Configuration	See <a href="#">3.2.1. Boot Configuration</a> on page <a href="#">47</a> .
PCI Express Configuration	See <a href="#">3.2.2. PCI Express Configuration</a> on page <a href="#">47</a> .
USB Configuration	See <a href="#">3.2.3. USB Configuration</a> on page <a href="#">47</a> .
Video Configuration	See <a href="#">3.2.4. Video Configuration</a> on page <a href="#">48</a> .
SATA Configuration	See <a href="#">3.2.5 SATA Configuration</a> on page <a href="#">48</a> .
ACPI Table/Feature Control	See <a href="#">3.2.6 ACPI Table/Feature Control</a> on page <a href="#">49</a> .
SIO FINTEK71869E	See <a href="#">3.2.7. SIO FINTEK71869E</a> on page <a href="#">50</a> .



### 3.2.1. Boot Configuration

Setting	Description
Numlock	Select Power-on state for Num lock

### 3.2.2. PCI Express Configuration

Configures PCI Express by the following settings:

Setting	Description
PCI Express Root Port 1/2/3/4	<ul style="list-style-type: none"> <li>▶ PCI Express Root Port Enables/disables this PCIe port.</li> <li>▶ PCIe Speed Options are: Auto, Gen 1, Gen 2 Auto is the default.</li> <li>▶ ASPM Support Options are: Disable : disables ASPM L0s : force all links to L0s state L1 : force all links to L1 state L0sL1 : force all links to L0s+L1 state Auto : BIOS auto configure</li> </ul>

### 3.2.3. USB Configuration

Select this submenu to view the status of the USB ports and configure USB features.

The featured settings are:

Setting	Description
XHCI Pre-Boot Mode Support	Enables/Disables XHCI Pre-Boot mode support
xHCI Mode	Set the mode of operation of xHCI controller Options are Disabled/Enabled/Auto/Smart Auto(default)
XHCI Controller	Enables/Disables XHCI controller
USB2 Link Power Management	Enables/Disables USB2 Link Power Management.
XHCI Streams	Enables/disables XHCI Stream
USB OTG Support	Enables/disables USB OTG Support
USB VBUS	Turn ON/OFF USB VBUS. Turn ON in HOST mode, and turn OFF in OTG device mode.
USB RMH Mode	Enables/disables USB RMH Mode
USB ECHI debug	Enables/disables USB ECHI debug
USB Per-Port Control	Enables/Disables USB Per-port control

### 3.2.4. Video Configuration

Configure video settings

The featured setting is:

Setting	Description
<b>Configure DDI1 as</b>	Set the hardware configuration of DDI1 Options are LVDS (default) / No device

#### 3.2.4.1 PTN3460 (eDP to LVDS) Configuration

Setting	Description
<b>PTN3460 Output Format</b>	Set the Output Format of PTN3460. Options are (00) VESA (24bpp) / (01) VESA or JEIDA (18bpp) / (10) JEIDA (24bpp) / (11) JEIDA (24bpp)
<b>PTN3460 Channel Control</b>	Set the Channel of PTN3460. Options are Single(default), Dual.
<b>PTN3460 EDID Table</b>	Set the EDID Table of PTN3460.

#### 3.2.4.2 IGD- LCD Control

Setting	Description
<b>GMCH BLC Control</b>	Set the mode of GMCH BLC Control Options are Auto(default) / PWM-Inverted

### 3.2.5 SATA Configuration

Select this submenu to configure the SATA controller and HD.

Setting	Description
<b>SATA Controller(s)</b>	Enables/disables the present SATA controller. ▶ <b>Enabled</b> is the default.
<b>Configures SATA Mode</b>	Configures how to run the SATA drives. ▶ Options available are <b>AHCI</b> (default) and <b>IDE</b> .
<b>SATA Port 0 Hot Plug Capability</b>	Enables/disables hot-pluggable feature for the SATA port.
<b>SATA Port 1 Hot Plug Capability</b>	▶ <b>Enabled</b> is the default.
<b>SATA Port 0 Connect to an ODD</b>	Enables/disables the SATA port connect to an ODD If enabled, when you connect an ODD to a SATA port.
<b>SATA Port 1 Connect to an ODD</b>	The software auto detection for media insert and tray will be enabled. ▶ <b>Disabled</b> is the default.
<b>Serial ATA Port 0</b>	Delivers the SATA port Media information and Security Mode.
<b>Serial ATA Port 1</b>	

### 3.2.6 ACPI Table/Feature Control

Setting	Description
<b>FACP - RTC S4 Wakeup</b>	This function will be available only when ACPI is enabled. Enables/disables S4 Wakup from RTC.
<b>APIC - IO APIC Mode</b>	This item is valid only for WIN2K and WINXP. Also, a fresh install of the OS must occur when APIC mode is desired. Enables/disables the APIC mode
<b>DSDT - ACPI S3</b>	Enables/disables ACPI S3 state
<b>DSDT - ACPI S4</b>	Enables/disables ACPI S4 state
<b>BGRT - ACPI BGRT</b>	Enables/disables ACPI BGRT Table


### 3.2.7. SIO FINTEK71869E

Configures SIO by the following settings:

Setting	Description
<b>Power Loss mode</b>	Set the state of Power Loss mode Options are Keep last state/ Bypass mode/ Always On(default)/Always Off
<b>Serial Port A</b>	<ul style="list-style-type: none"> <li>▶ Serial Port A Enables/disables the Serial port.</li> <li>▶ RS-232/RS-485 Setting Set the mode of Serial port. Options are RS232 (default), RS485</li> <li>▶ Base I/O Address Setup the Base I/O Address of the Serial Port.</li> <li>▶ Interrupt Setup the Interrupt of the Serial Port</li> </ul>
<b>Serial Port B</b>	<ul style="list-style-type: none"> <li>▶ Serial Port B Enables/disables the Serial port.</li> <li>▶ RS-232/RS-485 Setting Set the mode of Serial port. Options are RS232 (default), RS485</li> <li>▶ Base I/O Address Setup the Base I/O Address of the Serial Port.</li> <li>▶ Interrupt Setup the Interrupt of the Serial Port</li> </ul>

### 3.3. Security

The **Security** menu sets up the password for the system’s administrator account. Once the administrator password is set up, this BIOS Setup utility is limited to access and will ask for the password each time any access is attempted.




The featured setting is:

Setting	Description
<b>Set Supervisor Password</b>	<p>To set up an administrator password:</p> <ol style="list-style-type: none"> <li>1. Select <b>Set Supervisor Password</b>. An <b>Create New Password</b> dialog then pops up onscreen.</li> <li>2. Enter your desired password that is no less than 3 characters and no more than 20 characters.</li> <li>3. Hit [Enter] key to submit.</li> </ol>

### 3.4. Power

The **Power** menu sets up the power option of system




The featured setting is:

Setting	Description
Wake on PME	Enables or disables Wake on PME. Determines the action taken when the system power is off and a PCI Power Management Enable wake up event occurs.

### 3.5. Boot

The **Boot** menu configures how to boot up the system such as the configuration of boot device priority.




The featured settings are:

Setting	Description
<b>Boot Type</b>	Select the boot type. Options are Legacy Boot Type (default), and UEFI Boot Type.
<b>Quick Boot</b>	Allow InsydeH20 to Skip certain tests while booting . This will decrease the time need to boot the system.
<b>Quiet Boot</b>	Disables or enables booting in text mode.
<b>PXE boot to LAN</b>	Disables or enables PXE boot to LAN.
<b>ACPI Selection</b>	Select boot to Acpi 3.0/Acpi 1.0B Options are Acpi 1.0B/Acpi 3.0/Acpi 4.0/Acpi 5.0
<b>USB Boot</b>	Disables or enables booting to USB boot devices.
<b>Automatic Failover</b>	Enables/disables the Automatic Failover.

### 3.6. Exit

The **Save & Exit** menu features a handful of commands to launch actions from the BIOS Setup utility regarding saving changes, quitting the utility and recovering defaults.



The features settings are:

Setting	Description
<b>Exit Saving Changes</b>	Saves the changes and quits the BIOS Setup utility.
<b>Save Changes Without Exit</b>	Save Changes but does not quit the BIOS.
<b>Exit Discard Changes</b>	Quits the BIOS Setup utility without saving the change(s).
<b>Load Optimal Defaults</b>	Restores all settings to defaults. ▶ This is a command to launch an action from the BIOS Setup utility rather than a setting.
<b>Load Custom Default</b>	Load custom default values
<b>Save Custom Default</b>	Save current setting as custom default
<b>Discard Changes</b>	Discard all changes without Exit.



---

# Appendices

---

### Appendix A. Watchdog Timer (WDT) Setting

The application software depends on its requirement to trigger WDT with adequate timer setting. Before WDT timeout, the functional normal system will reload the WDT. The WDT never time-out for a normal system. The WDT will not be reloaded by an abnormal system, then WDT will time-out and auto-reset the system to avoid abnormal operation.

This computer supports 255 levels watchdog timer by software programming I/O ports.

Below is an program example to disable and load WDT.

#### Sample Codes:

```
/*----- Include Header Area -----*/
#include "math.h"
#include "stdio.h"
#include "dos.h"

unsigned char sioIndex = 0x2E;          /* or index = 0x4E */
unsigned char sioData = 0x2F;         /* or data = 0x4F */

/*----- routing, sub-routing -----*/
void main()
{
    outportb(sioIndex, 0x87);          /* Enable Super I/O */
    outportb(sioIndex, 0x87);

- WDT */
    outportb(sioIndex, 0x07);          /* Select logic device
    outportb(sioData, 0x07);

    outportb(sioIndex, 0x30);          /* Enable WDT */
    outportb(sioData, 0x01);

Output */
    outportb(sioIndex, 0xF0);          /* Enable WDRST#
    outportb(sioData, 0x80);

value */
    outportb(sioIndex, 0xF6);          /* Set WDT Timeout
    outportb(sioData, 0x05);

    outportb(sioIndex, 0xF5);          /* Set Configure and
Enable WDT timer, Start countdown */
    outportb(sioData, 0x32);

    outportb(sioIndex, 0xAA);          /* SIO - Disable */
}
```

## Appendix B. Digital I/O Setting

Below are the source codes written in C, please take them for Digital I/O application examples. The default I/O address is 6Eh.

```

/*----- Include Header Area -----*/
#include "math.h"
#include "stdio.h"
#include "dos.h"

#define   sioIndex           0x2E           /* or 0x4E */
#define   sioData           0x2F           /* or 0x4F */

/*----- routing, sub-routing -----*/
void main()
{
    int iData;

    SioGPIOMode(0x0F);
    delay(2000);

    SioGPIOData(0x05);
    delay(2000);

    iData = SioGPIOStatus();
    printf(" Input : %2x \n",iData);
    delay(2000);

    SioGPIOData(0x0A);
    delay(2000);

    iData = SioGPIOStatus();
    printf(" Input : %2x \n",iData);
    delay(2000);
}

void SioGPIOMode(int iMode)
{
    outputb(sioIndex,0x87);           /* Enable Super I/O */
    outputb(sioIndex,0x87);

    outputb(sioIndex,0x07);           /* Select logic device – GPIO */
    outputb(sioData, 0x06);

    outputb(sioIndex,0x30);           /* Enable GPIO */
    outputb(sioData, 0x01);

    outputb(sioIndex,0xC0);           /* GPIO3 0~7 - Output Enable */
    outputb(sioData,iMode);

    outputb(sioIndex,0xAA);           /* Disable Super I/O */
}

```

## Appendices

---

```
}
```

```
void SioGPIOData(int iData)
```

```
{  
    outputb(sioIndex,0x87);           /* Enable Super I/O */  
    outputb(sioIndex,0x87);  
  
    outputb(sioIndex,0x07);         /* Select logic device – GPIO */  
    outputb(sioData, 0x06);  
  
    outputb(sioIndex,0xC1);         /* GPIO3 0~7 - Output Data */  
    outputb(sioData,iData);  
  
    outputb(sioIndex,0xAA);        /* Disable Super I/O */  
}
```

```
int SioGPIOStatus()
```

```
{  
    int iStatus;  
  
    outputb(sioIndex,0x87);         /* Enable Super I/O */  
    outputb(sioIndex,0x87);  
  
    outputb(sioIndex,0x07);         /* Select logic device – GPIO */  
    outputb(sioData, 0x06);  
  
    outputb(sioIndex,0xC2);         /* GPIO3 0~7 - Status */  
    iStatus = inportb(sioData);  
  
    outputb(sioIndex,0xAA);        /* Disable Super I/O */  
  
    return iStatus;  
}
```

## Appendix C: I/O Port Address Map

Each peripheral device in the system is assigned a set of I/O port addresses which also becomes the identity of the device.

The following table lists the I/O port addresses used.

Address	Device Description
0x000003F8-0x000003FF	Communications Port (COM1)
0x000002F8-0x000002FF	Communications Port (COM2)
0x00002000-0x000020FF	Ethernet Controller
0x00001000-0x000010FF	Ethernet Controller
0x00000060-0x00000060	Microsoft PS/2 Mouse
0x00000064-0x00000064	Microsoft PS/2 Mouse
0x00000070-0x00000077	Motherboard resources
0x0000002E-0x0000002F	Motherboard resources
0x0000004E-0x0000004F	Motherboard resources
0x00000061-0x00000061	Motherboard resources
0x00000063-0x00000063	Motherboard resources
0x00000065-0x00000065	Motherboard resources
0x00000067-0x00000067	Motherboard resources
0x00000080-0x0000008F	Motherboard resources
0x00000092-0x00000092	Motherboard resources
0x000000B2-0x000000B3	Motherboard resources
0x00000680-0x0000069F	Motherboard resources
0x00000400-0x0000047F	Motherboard resources
0x00000500-0x000005FE	Motherboard resources
0x00000000-0x0000006F	PCI bus
0x00000078-0x00000CF7	PCI bus
0x00000D00-0x0000FFFF	PCI bus
0x00002000-0x000020FF	PCI standard PCI-to-PCI bridge
0x00001000-0x000010FF	PCI standard PCI-to-PCI bridge
0x00000020-0x00000021	Programmable interrupt controller

## Appendices

---

0x00000024-0x00000025	Programmable interrupt controller
0x00000028-0x00000029	Programmable interrupt controller
0x0000002C-0x0000002D	Programmable interrupt controller
0x00000030-0x00000031	Programmable interrupt controller
0x00000034-0x00000035	Programmable interrupt controller
0x00000038-0x00000039	Programmable interrupt controller
0x0000003C-0x0000003D	Programmable interrupt controller
0x000000A0-0x000000A1	Programmable interrupt controller
0x000000A4-0x000000A5	Programmable interrupt controller
0x000000A8-0x000000A9	Programmable interrupt controller
0x000000AC-0x000000AD	Programmable interrupt controller
0x000000B0-0x000000B1	Programmable interrupt controller
0x000000B4-0x000000B5	Programmable interrupt controller
0x000000B8-0x000000B9	Programmable interrupt controller
0x000000BC-0x000000BD	Programmable interrupt controller
0x000004D0-0x000004D1	Programmable interrupt controller
0x00003000-0x0000301F	SM Bus Controller
0x00003048-0x0000304F	Standard AHCI 1.0 Serial ATA Controller
0x0000305C-0x0000305F	Standard AHCI 1.0 Serial ATA Controller
0x00003040-0x00003047	Standard AHCI 1.0 Serial ATA Controller
0x00003058-0x0000305B	Standard AHCI 1.0 Serial ATA Controller
0x00003020-0x0000303F	Standard AHCI 1.0 Serial ATA Controller
0x00000060-0x00000060	Standard PS/2 Keyboard
0x00000064-0x00000064	Standard PS/2 Keyboard
0x00003050-0x00003057	Standard VGA Graphics Adapter
0x000003B0-0x000003BB	Standard VGA Graphics Adapter
0x000003C0-0x000003DF	Standard VGA Graphics Adapter
0x00000070-0x00000077	System CMOS/real time clock
0x00000040-0x00000043	System timer
0x00000050-0x00000053	System timer

## Appendix D: Interrupt Request Lines (IRQ)

Peripheral devices use interrupt request lines to notify CPU for the service required. The following table shows the IRQ used by the devices on board.

Level	Function
IRQ0	System timer
IRQ1	Standard PS/2 Keyboard
IRQ3	Communications Port (COM2)
IRQ4	Communications Port (COM1)
IRQ7	PCI Encryption/Decryption Controller
IRQ8	High precision event timer
IRQ10	Ethernet Controller
IRQ10	SM Bus Controller
IRQ11	Ethernet Controller
IRQ11	Universal Serial Bus (USB) Controller
IRQ12	Microsoft PS/2 Mouse
IRQ16	PCI standard PCI-to-PCI bridge
IRQ17	PCI standard PCI-to-PCI bridge
IRQ18	SDA Standard Compliant SD Host Controller
IRQ18	PCI standard PCI-to-PCI bridge
IRQ19	Standard AHCI 1.0 Serial ATA Controller
IRQ19	PCI standard PCI-to-PCI bridge
IRQ22	High Definition Audio Controller
IRQ23	SDA Standard Compliant SD Host Controller
IRQ23	Standard Enhanced PCI to USB Host Controller
IRQ48	
IRQ49	
IRQ50	
IRQ81~190	Microsoft ACPI-Compliant System

## Appendix E: Memory Mapping

Address	Device Description
0x90504000-0x90504FFF	Ethernet Controller
0x90500000-0x90503FFF	Ethernet Controller
0x90404000-0x90404FFF	Ethernet Controller
0x90400000-0x90403FFF	Ethernet Controller
0x90810000-0x90813FFF	High Definition Audio Controller
0xFED00000-0xFED003FF	High precision event timer
0xFF000000-0xFFFFFFFF	Intel(R) 82802 Firmware Hub Device
0xFED0C000-0xFED0CFFF	Motherboard resources
0xE0000000-0xEFFFFFFF	Motherboard resources
0xFED01000-0xFED01FFF	Motherboard resources
0xFED03000-0xFED03FFF	Motherboard resources
0xFED04000-0xFED04FFF	Motherboard resources
0xFED08000-0xFED08FFF	Motherboard resources
0xFED1C000-0xFED1CFFF	Motherboard resources
0xFEE00000-0xFEEFFFFFFF	Motherboard resources
0xFE000000-0xFEFFFFFFF	Motherboard resources
0xFED40000-0xFED44FFF	Motherboard resources
0x80000000-0x8FFFFFFF	PCI bus
0xA0000-0xBFFFF	PCI bus
0xC0000-0xDFFFF	PCI bus
0xE0000-0xFFFFF	PCI bus
0x90700000-0x907FFFFFFF	PCI Encryption/Decryption Controller
0x90600000-0x906FFFFFFF	PCI Encryption/Decryption Controller
0x90500000-0x90503FFF	PCI standard PCI-to-PCI bridge
0x90400000-0x90403FFF	PCI standard PCI-to-PCI bridge
0x90817000-0x90817FFF	SDA Standard Compliant SD Host Controller
0x90816000-0x90816FFF	SDA Standard Compliant SD Host Controller
0x9081A000-0x9081AFFF	SDA Standard Compliant SD Host Controller
0x90819000-0x90819FFF	SDA Standard Compliant SD Host Controller



---

0x90815000-0x9081501F	SM Bus Controller
0x90818000-0x908187FF	Standard AHCI 1.0 Serial ATA Controller
0x90814000-0x908143FF	Standard Enhanced PCI to USB Host Controller
0x90000000-0x903FFFFFF	Standard VGA Graphics Adapter
0x80000000-0x8FFFFFFF	Standard VGA Graphics Adapter
0xA0000-0xBFFFF	Standard VGA Graphics Adapter
0x90800000-0x9080FFFF	Universal Serial Bus (USB) Controller
0xFED0C000-0xFED0CFFF	
0xFED0D000-0xFED0DFFF	
0xFED0E000-0xFED0EFFF	

---